


WIT 50-100kW US Storage Inverter

WIT 50-100K-A-US, WIT 50-100K-AU-US

- Scalable system configuration, extend to 300kW
- Support UPS function and black start
- 100% unbalanced load when backup
- 110% continuous AC overloading capacity
- Support remote control of DG
- Grid-support functions



Preliminary Version

P O W E R
- I N G
T O M O -
R R O W O

GROWATT

<https://us.growatt.com>

Datasheet	WIT 50K-A-US WIT 50K-AU-US	WIT 63K-A-US WIT 63K-AU-US	WIT 75K-A-US WIT 75K-AU-US	WIT 100K-A-US WIT 100K-AU-US
Output Data (AC)				
AC nominal power	50kW	63kW	75kW	100kW
Max. AC apparent power	55kVA	69.3kVA	82.5kVA	110kVA
Nominal AC voltage	480V			
AC voltage range	-15%~+10%			
AC grid frequency	60 Hz			
AC grid frequency range	55-65Hz			
Max. output current	66.2A	83.4A	99.3A	132.4A
Adjustable power factor	-1...+1			
THDi	<3%			
AC grid connection type*1	3P3W+PE/3P4W+PE			
Input Data(AC)				
AC nominal power	50kW/100kW	63kW/126kW	75kW/150kW	100kW/200kW
Max. AC apparent power	55kVA/100kVA	69.3kVA/126kVA	82.5kVA/150kVA	110kVA/200kVA
Nominal AC voltage/range	480V, -15%~+10%			
Nominal AC grid frequency/range	60Hz,55-65Hz			
Max. input current	66.2A/120.3A	83.4A/151.6A	99.3A/180.5A	132.4A/240.7A
Adjustable power factor	-1...+1			
THDi	<3%			
AC grid connection type	3P3W+PE/3P4W+PE			
Battery Data (DC)				
Continuous charging and discharging power	56.7kW	71.4kW	85.1kW	113.5kW
Battery voltage range	750-1000V for 3P3W / 820-1000V for 3P4W			
Max charging and discharging current	75.6A	95.2A	113.5A	151.3A
BMS communication	RS485/CAN			
Types of Battery	Li-ion			
Backup Power (AC)*2				
Rated AC output power	50kW	63kW	75kW	100kW
Max. AC apparent power	60kVA	75.6kVA	90kVA	120kVA
Rated AC output voltage	277V(L-N) / 480V(L-L)			
Nominal AC output frequency	60 Hz			
Load connection*1	3P3W+PE/3P4W+PE			
Max. output current	72.2A	91A	108.3A	144.4A
THDv	<3% (Linear load)			
Load unbalance	100% three-phase unbalanced			
Overload capacity	≤110%: Continues; 110%~120%: 10min; >120%: 200ms			
On/off grid transfer time	≤16.6ms			
Efficiency				
MAX. Battery charge/discharge efficiency	98.2%			
Protection Devices				
Battery reverse protection	Yes			
AC/DC surge protection	Type II			
Insulation resistance monitoring	Yes			
Ground fault monitoring	Yes			
Grid monitoring	Yes			
Residual-current monitoring unit	Yes			
AC short-circuit protection	Yes			
Anti-islanding protection	Yes			
General				
Dimensions (W / H / D)	33.5/53.1/20.1inch (850/1350/510mm)			
Weight	308.6 lbs (140kg)			
Operating temperature range	-22°F~+140°F, >122°F derating			
Relative humidity	0~100%			
Altitude	≤13123ft(4000m)			
Topology	Transformerless			
Cooling	Smart air cooling			
Enclosure	IP66/NEMA 4X			
Display	OLED+LED/WIFI+APP			
Interfaces: RS485/CAN	Yes			
Interfaces: WIFI/4G/LAN	Opt			
Warranty (5/10 years)	Yes/Opt			
UL1741:2021, UL 1741 SA/SB:2020, IEEE1547:2018, IEEE1547.1:2020, HECO Rule 14, E-5000, CSIP, SA17-SA18, UL1998:2018, CEC, FCC Part 15				

*1 For 3P4W connection type, the inverter is only compatible with APX commercial battery.
*2 The parameter of backup power is only available for WIT 50-100K-AU-US model.
*2024 SHENZHEN GROWATT NEW ENERGY CO.,LTD All rights reserved. Subject to change without notice.